108R[™]

TRUCK STEEL RADIAL

APPLICATION

REGIONAL-HAUL, ALL-POSITION/STEER







The regional all-position/steer tire tested and proven to be a top performer in its class.

FEATURES AND BENEFITS

Specially Designed Shoulder optimizes shape to reduce shoulder ripping and tearing in abrasive applications, effectively lowering your cost per mile.

Premium Casing, our most resilient ever, including a 16-ply rating offers increased load capacity so you can carry more freight on every trip.

Sidewall Abrasion Guard reduces damage to the sidewall caused by accidental curbing and scrubbing in urban applications.

Rock Shield Platforms keep stones and debris out of the grooves to protect the casing for longer service life.



108R replaces: Michelin X Multi Energy Z • Goodyear Fuel Max RSA • Bridgestone R268 Ecopia

TIRE SIZE	PART NUMBER (Phasing Out)	PART NUMBER (New)	PLY Rating (L.R.)	TIRE WEIGHT (LBS)	RIM SIZE (INCH)		INFLATED DIMENSIONS		TREAD	LOADED DIMENSIONS			MAX LOAD CAPACITY AT COLD INFLATION PRESSURE		MAX
					MEASURE	ALT	OVERALL WIDTH (INCH)	OVERALL Diameter (Inch)	DEPTH (1/32")	SECTION WIDTH (INCH)	STATIC RADIUS (INCH)	RPM	LB/PSI Single	LB/PSI DUAL	SPEED (MPH)
295/75R22.5	10825	120110825	14G	115.1	9.00	8.25	11.6	40.3	22	12.6	18.9	517	6175@110	5675@110	75
295/75R22.5	10831	120110831	16H	116.6	9.00	8.25	11.6	40.3	22	12.6	18.9	517	7160@120	6610@120	75
11R22.5	10826	120110826	14G	118.3	8.25	7.50	10.9	41.6	22	12.0	19.4	502	6175@105	5840@105	75
11R22.5	10832	120110832	16H	118.4	8.25	7.50	10.9	41.6	22	12.0	19.4	502	6610@120	6005@120	75
285/75R24.5	10827	120110827	14G	119.2	8.25	7.50-9.00	11.1	41.5	22	12.0	19.5	501	6175@110	5675@110	75
11R24.5	10828	120110828	14G	121.7	8.25	7.50	11.0	43.7	22	12.1	20.4	478	6610@105	6005@105	75
11R24.5	10834	120110834	16H	121.7	8.25	7.50	11.0	43.7	22	12.1	20.4	478	7160@120	6610@120	75

For warranty information, please refer to the Yokohama Tire Warranty Claims Procedure Manual at http://www.yokohamatruck.com/warranty