




# GENERAL HD

LONG/SHORT HAUL, HIGHWAY TANDEM  
DRIVE AXLE



Smartway Verified



## FEATURES & BENEFITS

- ▶ Closed shoulder tread design delivers high mileage and optimal fuel economy.
- ▶ Deep 30/32" intermediate blocks deliver sustained traction in demanding applications.
- ▶ Improved bead design for better casing durability and retreadability.
- ▶ Stone ejection system reduces stone retention.

## TECHNICAL DATA

Tire Size	Load Range	Article Number	Tread Depth   32nds	Max Speed   MPH	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Unit MI (KM)	Tire Weight LB (KG)	Single Max. Load @ Inflation LB, PSI (KG, KPa)	Dual Max. Load @ Inflation LB, PSI (KG, KPa)
11R22.5	G	05210950000	30	75	19.6 (498)	42.1 (1069)	11.1 (282)	12.3 (312)	8.25, 7.50	12.5 (318)	492 (306)	123 (55)	6175 / 105 (2800 / 720)	5840 / 105 (2650 / 720)
11R22.5	H	05210960000	30	75	19.6 (498)	42.1 (1069)	11.1 (282)	12.3 (312)	8.25, 7.50	12.5 (318)	492 (306)	124 (56)	6610 / 120 (3000 / 830)	6005 / 120 (2725 / 830)
295/75R22.5	G	05211000000	30	75	19.1 (485)	40.9 (1039)	10.9 (277)	12.0 (305)	8.25, 9.00	12.5 (318)	506 (314)	118 (53)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)
11R24.5	G	05210970000	30	75	20.6 (523)	44.1 (1120)	11.1 (282)	12.3 (312)	8.25, 7.50	12.5 (318)	469 (292)	131 (59)	6610 / 105 (3000 / 720)	6005 / 105 (2725 / 720)
11R24.5	H	05210980000	30	75	20.6 (523)	44.1 (1120)	11.1 (282)	12.3 (312)	8.25, 7.50	12.5 (318)	469 (292)	133 (60)	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)
285/75R24.5	G	05210990000	30	75	19.7 (500)	42.1 (1069)	10.8 (274)	11.9 (302)	8.25	12.5 (318)	492 (306)	123 (56)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.