





GENERAL RA

ALL-POSITION SERVICE IN REGIONAL HAULING,
PICK-UP & DELIVERY, AND ON/OFF HIGHWAY



Smartway Verified



FEATURES & BENEFITS

- ▶ A hard-working regional, all-position tire featuring high removal mileage and even, reliable wear.
- ▶ Tread compounding provides resistance to abrasion, cutting and chipping in demanding regional applications.
- ▶ The General RA will deliver performance that lowers costs for your business and gives drivers confidence in demanding applications.

TECHNICAL DATA

Tire Size	Load Range	Article Number	Tread Depth 32nds	Max Speed MPH	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Unit MI (KM)	Tire Weight LB (KG)	Single Max. Load @ Inflation LB, PSI (KG, KPa)	Dual Max. Load @ Inflation LB, PSI (KG, KPa)
11R22.5	H	05122920000	20	75	19.3 (490)	41.4 (1052)	11.1 (281)	11.9 (302)	8.25, 7.50	12.5 (318)	500 (311)	118 (54)	6610 / 120 (3000 / 830)	6005 / 120 (2725 / 830)
295/75R22.5	H	05122910000	20	75	18.6 (472)	40.1 (1019)	11.0 (279)	12.5 (318)	8.25, 9.00	12.5 (318)	516 (321)	113 (51)	6940 / 120 (3150 / 830)	6175 / 120 (2800 / 830)
11R24.5	H	05122930000	20	75	20.3 (516)	43.4 (1103)	11.1 (281)	11.9 (302)	8.25, 7.50	12.5 (318)	477 (296)	128 (58)	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)
285/75R24.5	H	05122940000	20	75	19.3 (490)	41.3 (1049)	10.8 (274)	12.0 (305)	8.25	12.5 (318)	501 (311)	118 (53)	6780 / 120 (3075 / 830)	6175 / 120 (2800 / 830)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.