



GENERAL RD

LONG/SHORT HAUL, HIGHWAY SINGLE/TANDEM
DRIVE AXLE



FEATURES & BENEFITS

- ▶ An open shoulder drive tire that gives long life over short or long hauls with great traction.
- ▶ Innovative lug angle provides outstanding traction throughout the life of the tread.
- ▶ Tread design provides excellent wet/dry traction, resists irregular wear and reduces stone retention.

TECHNICAL DATA

Tire Size	Load Range	Article Number	Tread Depth 32nds	Max Speed MPH	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Unit MI (KM)	Tire Weight LB (KG)	Single Max. Load @ Inflation LB PSI (KG, KPa)	Dual Max. Load @ Inflation LB PSI (KG, KPa)
11R22.5*	G	05211030000	28	75	19.5 (495)	41.8 (1062)	11.3 (287)	12.1 (307)	8.25	12.5 (318)	495 (308)	122 (55)	6175 / 105 (2800 / 720)	5840 / 105 (2650 / 720)
11R22.5*	H	05211040000	28	75	19.5 (495)	41.8 (1062)	11.3 (287)	12.1 (307)	8.25	12.5 (318)	495 (308)	124 (56)	6610 / 120 (3000 / 830)	6005 / 120 (2725 / 830)
295/75R22.5*	G	05211080000	28	75	18.9 (480)	40.8 (1036)	11.0 (279)	12.2 (310)	8.25	12.5 (318)	509 (315)	116 (52)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)
11R24.5	G	05211050000	28	75	20.6 (523)	43.8 (1113)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	472 (293)	131 (59)	6610 / 105 (3000 / 720)	6005 / 105 (2725 / 720)
11R24.5	H	05211060000	28	75	20.6 (523)	43.8 (1113)	11.3 (287)	12.2 (310)	8.25	12.5 (318)	472 (293)	133 (60)	7160 / 120 (3250 / 830)	6610 / 120 (3000 / 830)
285/75R24.5	G	05211070000	28	75	19.6 (498)	42.0 (1066)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	493 (306)	120 (54)	6175 / 110 (2800 / 760)	5675 / 110 (2575 / 760)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC. reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.