

Legend:

			
3G Casing	SmartWay Verified	With TPMS Sensor	Retread Available

PRODUCT FEATURES ABOVE ONLY APPLY TO PRODUCTS IF THE MATCHING ICON IS DARKENED.

# HSR2 SA

## Regional All-Position

 GOODS  PEOPLE  CONSTRUCTION



### PRODUCT DATA



TIRE SIZE	LOAD RANGE	ARTICLE NUMBER	TREAD DEPTH (32nds)	MAX SPEED (MPH)	STATIC LOADED RADIUS		OVERALL INFLATED DIAMETER		OVERALL INFLATED WIDTH		LOADED SECTION WIDTH		APPROVED RIM(S)	MINIMUM DUAL SPACING		REVS PER UNIT		TIRE WEIGHT		MAX. LOAD @ INFLATION	
					IN	MM	IN	MM	IN	MM	IN	MM		IN	MM	MI	KM	LB	KG	SINGLE	DUAL
					LBS, PSI (KG, KPa)		LBS, PSI (KG, KPa)														
255/70R22.5*	H	05122460000	18	75	171	434	366	930	10.0	255	10.8	274	8.25, 7.50	11.3	287	565	351	91	41	5510, 120 (2500, 830)	5070, 120 (2300, 830)
275/70R22.5*	J	05121290000	18	75	178	451	379	962	10.7	272	11.6	295	8.25	12.4	315	547	340	115	52	6940, 130 (3150, 900)	6395, 130 (2900, 900)
295/80R22.5*	H	05123900000	20	81	19.3	490	414	1052	11.8	300	13.2	335	9.00, 8.25	12.5	318	500	311	138	63	7830, 120 (3550, 830)	6940, 120 (3150, 830)
315/80R22.5 *	L	05120980000	19	75	19.8	503	425	1080	12.5	317	12.5	317	9.00, 8.25	13.8	351	487	303	143	65	9090, 130 (4125, 900)	8270, 130 (3750, 900)

TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. \* - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. 315/80R22.5 tires used on 8.25" rims are restricted to a maximum of 7610 lbs at 120 psi. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.



Maximum tire life expectancy and wet traction capabilities through **customized tread geometry**.



**Superb wet traction** capabilities with minimum wear through innovative tread compound.



Ideal for buses and larger recreational vehicles.

**Applications:** Steer or all-position regional/long haul, for bus or large RV traffic.