

REGIONAL TO URBAN ALL-POSITION TIRE

The M143 is a rugged all-position tire designed for demanding regional and urban delivery service. Wide-belt construction and stable outer ribs contribute to long and even tread wear, while special heat-resistant compounds and stone-ejector grooves support extended tire and casing life. This base, regional to urban pickup and delivery tire combines product performance, application versatility, and a competitive acquisition point for a lower cost per mile, making the M143 a leading value alternative tire.

APPLICATION	RECOMMENDED	SUITABLE
LONG HAUL	STEER	DRIVE, TRAILER
REGIONAL	STEER	DRIVE, TRAILER
URBAN	STEER	DRIVE, TRAILER

LONG TREAD LIFE

- DSOC II™ technology optimizes footprint design for even wear and long life.
- Wide five-rib pattern with a solid outer rib and optimized tread depth combine for long, even wear.

EXCELLENT PERFORMANCE AND SAFETY

- Wide solid outer rib improves stability and handling performance.
- Zigzag pattern with deep tread depth improves wet and dry traction.

IMPROVED FUEL ECONOMY

- Optimized tread design reduces rolling resistance for improved fuel economy.

EXCEPTIONAL RETREADABILITY AND CASING DURABILITY

- Four-steel-belt construction braces the tread area, improving durability.
- High-elongation top belt protects casing integrity, while steel chafer bead offers improved durability.
- Advanced casing design and heat-resistant compounding deliver extended casing life and improved retreadability.



WHEEL DIA.	TIRE SIZE	LOAD RANGE/ PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)*	STATIC LOADED WIDTH (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
17.5	215/75R17.5	G/14	306100	81	(6.0)-6.75	58	16	30.6	8.3	14.2	9.1	3750	3530	105	105	679
	225/70R19.5	F/12	562060	87	(6.00)-6.75	65	16	32.1	8.3	14.7	9.1	3640	3415	95	95	647
	225/70R19.5	G/14	562050	87	(6.00)-6.75	65	16	32.1	8.3	14.7	9.1	3970	3750	110	110	647
19.5	245/70R19.5	H/16	562020	87	6.75-(7.50)	77	16	33.2	9.6	15.1	10.5	4940	4675	120	120	626
	265/70R19.5	G/14	562070	81	6.75-(7.5)-8.25	87	16	34.3	10.0	15.9	10.9	5510	5205	110	110	605
	285/70R19.5	H/16	562120	81	7.5-(8.25)-9.0	95	17	35.1	10.8	16.3	11.8	6395	6005	125	125	590

Bold designates measuring rim width.
*Inflated dimensions. Never exceed wheel manufacturer's load and inflation limits.