

Regional/Urban - Drive

G622 RSD®

Goodyear's Best Regional and Urban Traction Drive Tire

- Tough tread compounds
- Open shoulder tread design with aggressive blading
- Premium enhanced casing
- Tredlock blade technology



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm			
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	111	50	7.50	10.2	259	40.6	1,031	19.0	483	512	318	23	11.4	290	75		
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	119	54	8.25	11.1	282	42.0	1,067	19.7	500	497	309	26	12.5	318	75		
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	121	55	8.25	11.1	282	42.0	1,067	19.7	500	497	309	26	12.5	318	75		
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	134	61	8.25	11.1	282	43.9	1,115	20.6	523	475	295	26	12.5	318	75		
12R22.5	H	7,390	3,350	830	120	6,780	3,075	830	120	139	63	9.00	11.7	297	43.3	1,100	20.3	516	482	300	26	13.5	343	75		
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	93	42	7.50	9.6	244	37.6	955	17.7	450	552	343	23	11.0	279	75		
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	95	43	7.50	10.0	254	37.0	940	17.3	439	561	349	23	11.3	287	81		
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	110	760	101	46	7.50	10.0	254	38.9	988	18.3	465	534	332	23	11.6	295	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	114	52	8.25	11.2	284	40.8	1,036	19.1	485	512	318	26	12.9	328	75		