



BFGoodrich® HIGHWAY CONTROL® S




GO THE DISTANCE

BFGoodrich® tires are built to go the distance. Each tire is constructed with a premium casing and tread designed to enhance even wear.

LONG TREAD LIFE

Expect long tread life and exceptional even wear performance

- Improved shoulder rib with added micro sipes improves resistance to irregular wear.
- New tread design with optimized micro siping technology fights the onset of irregular wear across the tread.



MULTIPLE RETREAD LIVES

Legendary BFGoodrich® casing

- Excellent retreadability
- Variable groove wall helps reduce stone retention and extend casing life





GUARANTEED. OVER THE LONG HAUL.


If you are not completely satisfied with the BFGoodrich® Highway Control® S tire mileage performance in the first year or before 50% of its usable tread life – whichever comes first – we will reimburse 50% of your acquisition price per tire. (2)





ALL WEATHER CONFIDENCE

Serpentine flow-thru groove design for outstanding water evacuation





FUEL SAVINGS

New sidewall compounds designed for fuel efficiency without sacrificing wear. (3)





	Catalog	Tread Depth	Max. Speed (4)		Loaded Radius		Overall Diameter		Overall Width (5)		Approved Wheels (Measuring wheel	Min. Dual Spacing (5)		Revs Per	Max. Load Per Tire Single			Max. Load Per Tire Dual					
	Nange	ge Number	32nds	mph	km/h	in.	mm.	in.	mm.	in.	mm.	listed first)	in.	mm.	Mile	lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	31501	18	75	120	19.2	488	41.3	1048	11.2	285	8.25, 7.50	12.5	318	502	6175	105	2800	720	5840	105	2650	720
11R22.5	Н	86958	18	75	120	19.2	488	41.3	1048	11.2	285	8.25, 7.50	12.5	318	502	6610	120	3000	830	6005	120	2725	830
275/80R22.5	G	34011	18	75	120	18.6	473	39.9	1014	11.0	279	8.25, 7.50	12.2	311	519	6175	110	2800	760	5675	110	2575	760
11R24.5	G	34060	18	75	120	20.2	513	43.2	1097	11.3	287	8.25, 7.50	12.5	318	479	6610	105	3000	720	6005	105	2725	720
11R24.5	Н	15789	18	75	120	20.2	513	43.2	1097	11.3	287	8.25, 7.50	12.5	318	479	7160	120	3250	830	6610	120	3000	830
285/75R24.5	G	04155	18	75	120	19.3	490	41.2	1046	10.7	272	8.25, 7.50	12.2	311	502	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.

- (1) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer.
- (2) Please see BFGoodrichTruckTires.com > Reference Manuals > Warranties/Guarantees for details.
- (3) Based on internal rolling resistance tests using ISO 28580 test method comparing the BFGoodrich® ST244 vs. BFGoodrich® Highway Control® S tires in the 275/80R22.5 LRG size.
 (4) Exceeding the lawful speed limit is neither recommended nor endorsed.

Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

BFGoodrich® tires are subject to a continuous development program. BFGoodrich® Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligation.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit www.bfgoodrichtrucktires.com

in the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.

Application	Highway	Regio	nal	Urban	Coad	ch/Bus	On/ Off-Road			
Position	Stee	r		Drive		Trailer				
Recommended Application Acceptable Application										

» Take control today at BFGoodrichTruckTires.com

To Find Your Nearest BFGoodrich® Commercial Truck Tire Dealer Call: United States, 1-877-788-8899; Canada, 1-888-871-6666 or visit www.bfgoodrichtrucktires.com © 2019 MNA, Inc. All rights reserved. BWL30000 (01/19)

© 2019 MNA(C)I All rights reserved. (02/19)