

OFF-ROAD COMMERCIAL GRADE TIRE

The iconic M-55 might be the hardest-working member of your crew. This commercial grade tire was built to handle the toughest of off-road jobs through snow, mud, and rough terrain. Its extreme durability and long tread life provide heavy-duty truck owners with dependable year-round service.

LT

LIGHT TRUCK / SUV / CUV

POPULAR FITMENTS

Chevrolet Silverado 2500
Ram Series
Ford F-250/F-350
Ford E-Series

AGGRESSIVE LUG AND BLOCK TREAD DESIGN

- Provides solid handling and traction.

OPEN SHOULDER DESIGN

- Maximizes water evacuation for excellent all-terrain traction and stability.

AGGRESSIVE SIPING

- Improves wet and snow traction.

PINNED FOR STUDS

- Able to accept TSMI #15 studs to aid in ice traction.



SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
15	LT215/75R15	100/97Q	C	BSW	309290	5.5-(6.0)-7.0	30	17.0	27.7	8.5	1765	1610	50	751
	LT235/75R15	104/101Q	C	BSW	309270	6.0-(6.5)-7.0	37	17.6	28.9	9.3	1985	1820	50	720
16	LT215/85R16	115/112Q	E	BSW	312270	5.5-(6.0)-7.0	43	17.0	30.7	8.7	2680	2470	80	676
	LT225/75R16	115/112Q	E	BSW	312350	(6.0) -7.0	40	17.0	29.4	8.7	2680	2470	80	705
	LT235/85R16	120/116Q	E	BSW	312290	6.0-(6.5)-7.5	49	17.5	32.0	9.3	3042	2770	80	650
	LT245/75R16	120/116Q	E	BSW	312330	6.5-(7.0)-8.0	46	17.5	30.8	9.8	3042	2778	80	675
	LT255/85R16	123/120Q	E	BSW	312230	6.5-(7.0)-8.0	59	18.1	33.4	10.4	3415	3085	80	622
	LT265/75R16	123/120Q	E	BSW	312250	7.0-(7.5)-8.0	58	18.3	32.0	10.8	3415	3085	80	649
	LT285/75R16	126/123Q	E	BSW	312240	7.5-(8.0)-9.0	60	18.9	33.2	11.2	3740	3415	80	626
17	LT235/80R17	120/117Q	E	BSW	312210	6.0-(6.5)-7.5	49	17.6	32.0	9.3	3085	2835	80	649
	LT245/75R17	121/118Q	E	BSW	312190	6.5-(7.0)-7.5	49	17.6	31.9	9.7	3195	2910	80	651
	LT265/70R17	121/118Q	E	BSW	312220	7.0-(8.0)-8.5	53	18.3	32.0	10.6	3195	2910	80	648
	LT285/70R17	121/118Q	E	BSW	301750	7.5-(8.5)-9.0	53	18.9	33.1	11.4	3195	2910	80	627
18	LT265/70R18	124/121Q	E	BSW	312200	7.0-(8.0)-9.0	57	18.3	33.0	10.6	3525	3195	80	629
	LT275/65R18	123/120Q	E	BSW	312300	7.5-(8.0)-9.0	57	18.9	32.4	11.0	3415	3085	80	640
	LT275/70R18	125/122Q	E	BSW	312310	7.0-(8.0)-8.5	60	18.8	33.6	11.0	3640	3305	80	619

LIGHT TRUCK / SUV / CUV

LT

Speed rated "Q" = 99mph, "M" = 81mph, "N" = 87 mph, "C" = 6-ply rating, "E" = 10-ply rating. "BSW" = Black Sidewall. Bold designates measuring rim width. *Inflated dimensions.