

## REGIONAL TO URBAN SUPER SINGLE TIRE

The M149 is an all-position super single tire designed to deliver superior wear performance in tough operations, ranging from urban front axles to long haul trailers. Optimized construction and tread design deliver high uniformity, even wear, and excellent wet traction. These benefits, combined with a competitive acquisition point, make the M149 a leading value alternative tire for tough operating conditions.

M149

APPLICATION	RECOMMENDED	SUITABLE
REGIONAL	STEER	DRIVE, TRAILER
URBAN	STEER	DRIVE, TRAILER

### LONG TREAD LIFE

- Optimized profile minimizes casing growth of the tread area for long wear life.
- Six straight and stiff ribs provide smooth wear and long life.

### EXCELLENT PERFORMANCE AND SAFETY

- Five wide grooves with siping on ribs provide outstanding wet traction.
- Exceptional uniformity and balance contribute to smooth ride.

### SUPERIOR CASING DURABILITY

- Wide steel-belt construction braces the tread area, improving durability, while high-elongation top belt protects casing integrity.
- High-stiffness bead filler for improved sidewall durability.



WHEEL DIA.	TIRE SIZE	LOAD RANGE/ PLY RATING	PRODUCT CODE	MAX SPEED (MPH)	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS.)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	STATIC LOADED RADIUS (IN.)*	STATIC LOADED WIDTH (IN.)	MAX LOAD (LBS.) SINGLE	MAX LOAD (LBS.) DUAL	MAX PRESSURE (PSI) SINGLE	MAX PRESSURE (PSI) DUAL	REVS PER MILE
22.5	385/65R22.5	L/20	562010	68	<b>(11.75)</b> -12.25	167	20	42.5	14.8	19.8	16.1	9920	-	130	-	489
22.5	425/65R22.5	L/20	562090	68	11.75- <b>(12.25)</b> -13.00	191	21	44.7	16.3	19.9	17.8	11400	-	120	-	464

Bold designates measuring rim width.  
\*Inflated dimensions. Never exceed wheel manufacturer's load and inflation limits.