

Regional/Urban - Steer/All Position

Marathon® RSA®

Regional and Urban All-Position Tire for Long Miles to Removal

- Dependable high scrub compounds
- Solid 5-rib tread design
- Enhanced casing
- Tredlock blade technology



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width			Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	32nds			in	mm			
TUBELESS TIRES ON 15° DROP CENTER RIMS																										
10R22.5	G	5,675	2,575	115	790	5,355	2,430	115	790	111	50	0.00	0.0	0	0.0	0	18.9	480	514	319	21	11.4	290	75		
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	120	54	8.25	10.8	274	41.8	1,062	19.5	495	497	309	22	12.5	318	75		
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	131	60	0.00	0.0	0	0.0	0	20.5	521	473	294	22	12.5	318	75		
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	141	64	0.00	0.0	0	0.0	0	20.1	511	482	300	22	13.5	343	75		
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	91	41	7.50	10.0	254	36.7	932	17.2	437	566	352	18	11.3	287	81		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	125	57	0.00	0.0	0	0.0	0	19.5	495	497	309	22	12.5	318	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	120	55	0.00	0.0	0	0.0	0	18.9	480	512	318	22	12.9	328	75		