

Mixed Service - Steer/All Position

Workhorse® MSA™

Mixed Service All-Position Tire for Long Miles to Removal in On- and Off-road Applications

- Dependable mixed service compounds
- Deep 22/32" tread depth
- Steel belt casing
- Stone protectors



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width	Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm			32nds	in	mm		
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	120	55	8.25	11.0	279	41.7	1,059	19.5	495	498	310	22	12.5	318	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	135	61	8.25	11.0	279	43.7	1,110	20.4	518	475	295	22	12.5	318	68	
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	150	68	8.25	11.3	287	45.1	1,146	21.1	536	461	287	22	13.2	335	68	
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	142	64	9.00	12.5	318	43.0	1,092	19.9	505	483	300	23	14.0	356	68	