



Improved mileage and exceptional handling, this all position tire delivers a smooth, quiet ride and long life for heavy delivery vehicles in regional and suburban service.

Improved Handling -

 New five rib tread design provides excellent water evacuation and traction

Excellent Mileage & Even Wear -

- Aggression resistant tread compound
- 7% wider footprint delivers 11% more rubber on the road,⁽¹⁾ enhancing vehicle stability and even wear

Improved Fuel Efficency –

• 13% reduction in rolling resistance (2)

Casing Durability - -

 Resistance to cuts, impacts and shocks through robust 5-belt casing design

 Michelin patented InfiniCoil[™] provides increased load capacity versus the MICHELIN[®] XFE[™] tire.



| | Size | Load Range | Catalog Number | Tread Depth | Max. Speed (*) | Loaded Radius | | Overall Diameter | | Overall Width (‡) | | Approved Wheels | Revs Per | Max. Load and Pressure Single | | | |
|---|------------|---------------|-------------------|----------------|----------------------|------------------|-----|---------------------|------|----------------------|-----|---------------------------------|-------------|----------------------------------|-----|------|-----|
| | | | | 32nds | mph | in. | mm | in. | mm | in. | mm | (Measuring wheel listed first.) | Mile | lbs. | psi | kg. | kPa |
| 3 | 85/65R22.5 | L | 26281 | 19 | 68 | 19.6 | 497 | 42.4 | 1078 | 15.1 | 384 | 11.75, 12.25 | 490 | 11000 | 130 | 5000 | 900 |

⁽¹⁾ Versus MICHELIN® XFE® tire.

Please consult wheel manufacturer's load and inflation limits. Never exceed wheel manufacturer's limits without permission of component manufacturer.











⁽²⁾ Based on commissioned third-party green house gas testing comparing the MICHELIN® X® MULTIWAY™ HD XZE® to the MICHELIN® XFE™. Actual on-road results may vary. Note: Wheel listed first is the measuring wheel.

^(*) Exceeding the lawful speed limit is neither recommended nor endorsed.

^(‡) Overall width will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

MICHELIN® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligations.