

The arrow with the larger head indicates the Michelin preferred direction of rotation for the tire, optimizing tread wear performance. We strongly recommend that, especially when new, Michelin® tires marked with a bi-directional arrow should be run in the direction of rotation

However, if a tire marked with the bi-directional arrow shows an irregular wear profile, (for example, a sloped wear pattern) then it may be turned on the rim and run in the direction of the smaller arrow head with no detriment to any other performance criteria. In cases such as this, Michelin recommends that all tires on the same axle should be turned on the rim such that all arrows face in the same direction. When turning these tires on the rim or moving from side to side on a vehicle, they should be treated in the same way as any other. Please remember that tires on the same axle must always be compatible with



An all position radial tire optimized for a wide spectrum of regional applications.

Increased Fuel Efficiency(1)

New tread compound lowers rolling resistance by 9% versus the MICHELIN® XZE®2+ tire.(2)

Reduced Irregular Wear

Directional tread design helps to reduce irregular wear.

Enhanced Casing Life

Groove bottom protectors and stone ejectors help to reduce stone drilling to extend casing life.

Extended Casing Life

to protect against shocks,





Size	Load Range	Catalog Number	Tread Depth			Loaded Radius		Overall Diameter		erall th (‡)	Approved Wheels (Measuring wheel	Min. Dual Spacing (‡)		Revs Per	Max. Load and Pressure Single			Max. Load and Pressure Dual				
			32nds	mph	in.	mm	in.	mm	in.	mm	listed first.)	in	mm	Mile	lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
265/70R19.5	G	75319	16	81*	15.8	401	34.0	864	10.2	259	7.50, 6.75	11.5	293	609	5510	112	2500	775	5205	112	2360	775
285/70R19.5	Н	31459	16	81*	16.2	411	35.2	893	10.7	273	8.25, 7.50, 9.00	12.2	309	591	6610	123	3000	850	6175	123	2800	850

Note: Wheel listed first is the measuring wheel.

Explanation of the meaning

MICHELIN® X® MULTI™ Z tire

indicated by the larger arrow head.

of the arrows for

each other

- (1) Based on industry standard rolling resistance testing of comparable tires or retreads. Actual results may vary, and may be impacted by many factors, to include road conditions, weather and environment, driver performance, etc.
- (2) 265/70R19.5 9% lower rolling resistance is in comparison to the 265/70R19.5 MICHELIN® XZE®2+ tire.
 285/70R19.5 18% lower rolling resistance is in comparison to the 285/70R19.5 MICHELIN® XZE®2+ tire.
 (3) 3PMSF (3 Peak Mountain Snow Flake) is from European R117 regulation. It has no regulatory Truck Tire reference in N.A. The tire must score at least 25% better in deep snow traction than the Standard Reference Test Tire on an ECE certified ISO test procedure. 3PMSF always appears with "M+S" mark.

 (*) Exceeding the lawful speed limit is neither recommended nor endorsed.
- (‡) Overall width will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly. MICHELIN® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change

product specifications at any time without notice or obligations.

Please consult wheel manufacturer's load and inflation limits. Never exceed wheel manufacturer's limits without permission of component manufacturer.

www.michelintruck.com

United States - Michelin North America, Inc., One Parkway South, Greenville, SC 29615, 1-888-622-2306 Canada - Michelin North America (Canada), Inc., 2500 Daniel Johnson, Suite 500, Laval, Quebec H7T 2P6, 1-888-871-4444 Mexico - Industrias Michelin, S.A. de C.V., Av. 5 de febrero No. 2113-A, Fracc. Industrial Benito Juarez, 7 6120, Querétaro, Qro. Mexico , 011 52 442 296 1600



